

ENGINEERED 4 SIMPLE USAGE & EASY SERVICE

UNIVERSAL MODULAR FRAME 4 VARIOUS PITCHES

UEFA COMPLIANCE WITH ULTIMATE PERFORMANCE

DIE-CAST ALU HOUSING 4 OPTIMAL HEAT EMISSION

HIGH REFRESH RATE, HIGH CONTRAST RATIO

CUTTING-EDGE LED ENHANCED TECHNOLOGY

PX-2-PX CALIBRATION WITH MOB FUNCTION

FRONT & REAR ACCESS 4 FLEXIBLE MAINTENANCE



Pixel pitch (mm)	4.7
LED type	SMD top LED
Panel size (WxHxD)	1,600x900x100
Panel resolution (px)	336x189
Panel weight (kg)	48
Brightness (nit)	6,000~8,000
Scan rate (scan)	1/7
Contrast ratio	3,000:1
Refresh rate (Hz)	3,840
Processing (bit)	22
Viewing angle (H/V)	140°/120°
Power consumption (W/panel)	980 (max)
Power input (Vac)	100~240
Max stacking/hanging (panel)	N/A
Service	Front & rear
Max power cascade (panel)	4 @ 230Vac
Max data cascade (panel)	10 @ 50Hz