

ENGINEERED 4 SIMPLE USAGE & EASY SERVICE

UNIVERSAL MODULAR FRAME 4 VARIOUS PITCHES

UEFA COMPLIANCE WITH ULTIMATE PERFORMANCE

DIE-CAST ALU HOUSING 4 OPTIMAL HEAT EMISSION

HIGH REFRESH RATE, HIGH CONTRAST RATIO

CUTTING-EDGE LED ENHANCED TECHNOLOGY

PX-2-PX CALIBRATION WITH MOB FUNCTION

FRONT & REAR ACCESS 4 FLEXIBLE MAINTENANCE



Pixel pitch (mm)	14.28
LED type	SMD top LED
Panel size (WxHxD)	1,600x900x100
Panel resolution (px)	112x63
Panel weight (kg)	48
Brightness (nit)	10,000
Scan rate (scan)	static
Contrast ratio	5,600:1
Refresh rate (Hz)	3,840
Processing (bit)	22
Viewing angle (H/V)	140°/100°
Power consumption (W/panel)	840 (max)
Power input (Vac)	100~240
Max stacking/hanging (panel)	N/A
Service	Front & rear
Max power cascade (panel)	4 @ 230Vac
Max data cascade (panel)	184 @ 50Hz